SLT Series Total Station

Data Specifications

ANGLE MEASUREMENT

Minimum Readout 1" (0.3 mgon), 5" (1.5 mgon), 10" (3 mgon)

Method Absolute encoding

Accuracy 1", 2", 5"
Compensator System Dual-axis
Compensator Range ±3'
Compensator Setting Accuracy 1"

DISTANCE MEASUREMENT WITH REFLECTOR

Single Prism3,000mThree Prisms5,000mReflective Sheet800m

 $\begin{array}{ccc} \textbf{Accuracy} & 2\text{mm} + 1.5\text{ppm} \\ \textbf{Measuring Time} & \text{Fine} & 1\text{s} \\ & \text{Quick} & 0.8\text{s} \end{array}$

Tracking 0.5s

DISTANCE MEASUREMENT WITHOUT REFLECTOR

 Range
 800m

 Single Prism
 > 7,500m

 Accuracy
 2mm + 2ppm

 Measuring Time
 1.5s

TELESCOPE

Magnification30xImageErect

Field of View 1°20′ (2.4m at 100m)

Min. Focusing Range 1.5m Reticle Illuminated

Effective Diameter of Objective 40mm/50mm (EDM)

LASER PLUMMET

Type Laser point, 4 brightness levels adjustment/

Optical plummet (optional)

1mm at 1.5m instrument height

Centering Accuracy

OPERATION

System Real-time operating system

DisplayDual face high resolution 256 colour displayKeyboard2 sides alpha-numerical back-lit keyboard

Temperature and Pressure Sensor Built-in

GENERAL

Environmental IP65 environmental protection

Humidity 95% (non-condensing)
Temperature -20°C to 50°C Operating

-40°C to 70°C Storage

Physical Properties Resolution 320 x 240 pixels

Weight ≤5.5kg (12lb) including battery

Battery 7.4VDC / 3000 mAH Operation Optimally 18 hours



MLT Series

Total Station





Building the Future with

Accuracy & Precision



Designed and Engineered in Sweden



Headquarters:

Datavägen 21B SE-436 32 Askim,Sweden info@satlabgps.com

Regional Offices:

Warsaw, Poland Jičín, Czech Republic Ankara, Turkey Scottsdale, USA Singapore Hong Kong Dubai, UAE

www.satlab.com.se

The SLT Series has a fast and powerful reflectorless EDM (0.8 seconds) that is designed to provide advanced accuracy with an efficient workflow in a sleek body. In order to ensure long-term operation in adverse weather conditions, various environmental tests such as vibration, drop, temperature, and humidity were performed to achieve the highest quality.











Maximum flexibility and great performance

Designed to overcome challenging work situations, Satlab has combined the best field technologies and specialized engineering features to ensure that the SLT Series provides the highest level of accuracy. Capture measurements faster and easier with our intuitive onboard software (Satcont) using a dual colour LCD display.



Applications

- Road Works
- Land Surveying
- Topography and As-built
- Construction Survey and Layout
- Foundation and Exterior



Increased efficiency with enhanced accuracy

The SLT Series is the most ideal entry-level work site surveying tool that offers flexibility and reliability, enabling you to get the job done without sacrificing on functionality. Equipped with a fast and reflectorless EDM, as well as the Satcont onboard software, the SLT Series is built to last.

Delivering quality equipment

Manufactured in an ISO, and CE certified factory, each total station is made with proper protocol and procedure that adheres to every operating aspect as well as stringent quality assurance checks that ensures the highest quality.

TECHNICAL SUPPORT

Satlab offers online resources and a professional support network available worldwide.











