







Headquarters: Datavägen 21B SE-436 32 Askim,SWEDEN info@satlabgps.com | www.satlabgps.com

Regional Offices: Jičín, CZECH REPUBLIC Ankara, TURKEY Scottsdale, USA Singapore, SINGAPORE Dresden, GERMANY Strasbourg, FRANCE



SL55+ GIS Data Collection





SATLAB



SL55+ Low Cost High Accuracy GNSS

The Ultimate GNSS Receiver for Geospatial Data Collection with High Accuracy























Low Cost Centimeter GNSS Receiver

SL55+ is a low cost GNSS receiver delivering high accuracy from centimeter to sub-meter depending on the applica-



Fast and Reliable Support Center

Swedish based central support office gives the fastest and the most reliable support for any kind of technical or service issue.

Complementary Solutions

SatLab offers a broad selection of Software packages for different applications with a large number of supported data formats in GIS and CAD.



Environment Friendly

All SatLab products are manufactured keeping the environment in mind. All electronics are RoHS certified and SatLab AB takes full responsibility for recycling end of life products.

Great Companion for Geospatial Data Collection

Selection of various mobile data collection software packages provide a solution for whatever your application requires. Any type of database structure or data requiring update is easy to manage.



GNSS

Multi Constellation GNSS

SL55+ is an advanced single frequency multi-constellation receiver, tracking Code & Carrier phase, and Doppler signals from GPS, Glonass, and Beidou satellites. This Multi constellation receiver enables you to obtain reliable positions in the most challenging environmental conditions.

Industrial Design

Weatherproof housing ensures trouble free operation in any conditions in the field. Sun readable and sensitive screen makes it easy to select even very tiny objects in the software interface.



- 72 channel GPS/GLONASS/BEIDOU (Carrier phase, Code phase & pseudo-range, Doppler)

- Operating System: Windows Mobile 6.5

- External Memory: MicroSD card up to 32 GB

- Screen: 3.7" color touch screen, Full VGA

- Support SBAS (WAAS, EGNOS, MSAS)
- Antenna: Internal and External (SMA)



Accuracy

- Real-Time
- Autonomous: 1-5 meters
- DGPS: Sub-meter

Processor: 806 Mhz

- Internal Flash Memory: 8 GB

- RAM: 256 MB

GNSS Features

- Post Processing
- Static: cm accuracy (external antenna + base within 25km)
- Kinematic: cm (external antenna needed + base within 10km)
- Kinematic: <30 cm (external antenna needed)
- Kinematic: sub-meter (with internal antenna)



Communication Interface

- Wi-Fi , Bluetooth
- 3G Internet
- Internal 5 megapixel camera
- MicroSD card slot (up to 32GB)



Power Supply

- Built-in 3.7V Lithium-Ion battery
- Battery life > 9 hours



Physical Properties - Size: 15.2 x 8.2 x 3.2 cm

- Weight: 320 gram (with battery)
- Operating Temperature: -20°C +70°C



